



Date issued 15/03/2007

## 8795-222 : SOFT FLEX ADDITIVE (10% RIGID OR 20% FLEXIBLE)



### SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

**Product Code:** 8795-222      **Product Name:** METALUX 2 SOFT FLEX ADDITIVE (10% RIGID OR 20% FLEXIBLE)  
**CAS No.:** Not applicable      **EC No.:** Not applicable      **UN No.:** 1263

	<u>SOUTH AFRICA</u>	<u>AUSTRALIA</u>	<u>UNITED STATES OF AMERICA</u>
<b>Company Name:</b>	Chemical Specialities (Pty) Ltd	Chemspec Coating (Pty) Ltd	Montana Products Inc.
<b>Address:</b>	320 South Coast Road Rossburgh Durban 4094	52-54 Chard Road Brookvale, NSW	9287 Smucker Road Orrville, Ohio 44667
<b>Telephone:</b>	+27 31 450-8800	+61 02 9907 1425	800-328-4892 (Toll Free)
<b>Facsimile:</b>	+27 31 450-8930	+61 02 9907 1465	001 3306693965
<b>Contact:</b>	Group Technical Manager <a href="mailto:techservice@chemspec.co.za">techservice@chemspec.co.za</a> <a href="http://www.chemspec.co.za">www.chemspec.co.za</a>	<a href="mailto:techservice@chemspec.co.za">techservice@chemspec.co.za</a>	<a href="mailto:techservice@chemspec.co.za">techservice@chemspec.co.za</a>

### SECTION 2. COMPOSITION / INFORMATION ON INGREDIENTS

**Chemical Class:** PAINT or PAINT RELATED  
**Classification:** - Xn R Phrases R10,66,67      S Phrases S43A  
**Comment:** OEL Type: Mixture - See tables in Sections 2 and 8

	<u>% m/m</u>	<u>EC Labels</u>	<u>CAS No.</u>	<u>EC No.</u>
<b>HAZARDOUS AND/OR OTHER RELEVANT COMPONENTS</b>				
n-BUTYL ACETATE	: %		123-86-4	607-025-00-1

### SECTION 3. HAZARDS IDENTIFICATION

**SAPMA Health Rating:** 3-SLIGHT - Irritation or minor reversible injury possible  
**Inhalation:** Irritating.  
**Skin:** Irritating, risk of dermatitis. May be absorbed.  
**Eyes:** Irritating.  
**Ingestion:** Irritating and nauseating.

No carcinogenic, mutagenic or genetic effects established  
May have short term environmental effects. Contain, monitor & remove

### SECTION 4. FIRST AID MEASURES

**Inhalation:** Move to fresh air.  
**Skin:** Use hand cleaner/soap & water. Remove contaminated clothing. If any discomfort get medical attention  
**Eyes:** Rinse immediately with plenty of water. Seek medical advice if symptoms persist.  
**Ingestion:** Wash mouth with plenty of water. Do NOT induce vomiting. Seek medical attention.

### SECTION 5. FIRE FIGHTING MEASURES

Flammable with toxic fumes.  
Containers liable to burst in a fire.  
Foam. CO2. Dry powder. Fog to cool and control. Do NOT use water jets.

### SECTION 6. ACCIDENTAL RELEASE MEASURES - SEE ALSO SECTIONS 5, 8, 13

Contain & collect. Use an inert - NOT sawdust. Keep out of drains and sewers.



## SECTION 7. HANDLING AND STORAGE

Store separately from any reactive substances - oxidisers in particular.  
No open flames. No smoking.  
Store containers with due care in case of fire.  
Subject to local bylaws.

## SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### HAZARDOUS AND/OR

### OTHER RELEVANT COMPONENTS:

	<u>CAS No.</u>	<u>OEL</u> (mg/m <sup>3</sup> )	<u>OEL</u> (ppm)	<u>STOEL</u> (mg/m <sup>3</sup> )	<u>STOEL</u> (PPM)	<u>OEL</u> Type
n-BUTYL ACETATE	123-86-4	710.	150.	950	200	RL

(CL/RL = Controlled/Recommended level 'S' = Skin annotation)

### SAPMA Rating:

### Inhalation:

### Skin:

### Eyes:

### Ingestion:

3-H-E PPE : Respirator and Eye protection

In case of insufficient ventilation, use respiratory protection.

Use barrier cream and impervious gloves.

Use face shield or goggles or face respirator/hood. Avoid direct contact.

Observe the rules of hygiene. Wash before eating, drinking or smoking.

OEL Type : Mixture - See tables in Sections 2 and 8



SAPMA - E

## SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

<b>Appearance:</b>	Viscous liquid	<b>Odour:</b>	Pungent
<b>Boiling Point:</b>	>35°C	<b>Flash Point:</b>	>23°C (derived)
<b>Water solubility:</b>	--	<b>Fat Solubility:</b>	--

## SECTION 10. STABILITY AND REACTIVITY

Stable under normal conditions

Inert - no reaction with fire-fighting water

## SECTION 11. TOXICOLOGICAL INFORMATION

No carcinogenic, mutagenic or genetic effects established  
LD50 Oral: >500 mg (Derived)

## SECTION 12. ECOLOGICAL INFORMATION

May have short term environmental effects. Contain, monitor & remove

## SECTION 13. DISPOSAL INFORMATION

Use reputable waste disposal contractors. Exercise caution in disposal of used containers.

## SECTION 14. TRANSPORT INFORMATION

<b>UN Number</b>	1263		
<b>Shipping Name</b>	PAINT or PAINT RELATED MATERIAL		
<b>IMO Class</b>	3.3	<b>Packing Group</b>	III
<b>Action Code</b>	127		
<b>HazChem</b>	3[Y]		
<b>Kemler Code</b>	30		





#### SECTION 15. REGULATORY INFORMATION

- EC No.:** - n/a Contains :  
- *R Phrases* R10,66,67 *S Phrases* S43A
- R10** - Flammable
- R66** - Repeated exposure may cause skin drying or cracking
- R67** - Vapours may cause drowsiness and dizziness.
- S43A** - In case of fire, use water fog, foam or powder - Do not use water jets!

#### SECTION 16. OTHER INFORMATION

TAKE PRECAUTIONARY MEASURES AGAINST STATIC DISCHARGES.  
IN CASE OF ANY DISCOMFORT ALWAYS SEEK MEDICAL ADVICE.

This MSDS conforms with General Administrative Regulations of 6 Sept.1996 (ISO-11014/ANSIZ400.1.1996)  
OELs derived from OHS Act Regulations for Dangerous Chemical Substances of 25 Aug.1995 (EH-42)  
SAPMA Rating - South African Paint Manufacturers Association Guide to Health Hazards (SABS ARP 006:1991)  
All information is given in good faith but without guarantee in respect of accuracy.  
No responsibility is accepted for errors or omissions or the consequences thereof.

(Date of issue : 15/03/2007

Date of analysis : 15/03/2007)