

HYDROLUX MIXED COLOURS



SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product Code	rgb2551_2548	Product Name	Hydrolux Mixed Colours	
CAS No.	Not applicable	EC No	Not applicable	UN No Not applicable

SECTION 2. COMPOSITION/INFORMATION ON INGREDIENTS

Classification EC Classification : Not classified as hazardous
Comment OEL Type : Mixture - See tables in Sections 2 and 8

	% m/m	EC Labels	CAS No.	EC No.
HAZARDOUS AND/OR OTHER RELEVANT COMPONENTS				
2-BUTOXYETHANOL	OEL	Xn	111-76-2	603-014-00-0
XYLENE	OEL	Xn	1330-20-7	601-022-00-9

SECTION 3. HAZARDS IDENTIFICATION

SAPMA Health Rating 3-SLIGHT - Irritation or minor reversible injury possible
Inhalation Avoid exposure to vapours, fumes and mists.
Skin Irritating, risk of dermatitis. May be absorbed.
Eyes Irritating.
Ingestion Irritating and nauseating.
 No carcinogenic, mutagenic or genetic effects established
 May have short term environmental effects. Contain, monitor & remove

SECTION 4. FIRST AID MEASURES

Inhalation Move to fresh air.
Skin Use hand cleaner/soap & water. Remove contaminated clothing. If any discomfort get medical attention
Eyes Rinse immediately with plenty of water. Seek medical advice if symptoms persist.
Ingestion Wash mouth with plenty of water. Do NOT induce vomiting. seek medical attention.

SECTION 5. FIRE FIGHTING MEASURES


Non-combustible. Gives off toxic fumes at high temperatures.
 No direct explosion hazard expected.
 Cool with water spray or fog. Contain run-off - keep out of Storm water drains.

SECTION 6. ACCIDENTAL RELEASE MEASURES - SEE ALSO SECTIONS 5, 8, 13

Contain & collect. Keep out of drains and sewers

SECTION 7. HANDLING AND STORAGE

Store only in designated places.
 Store away from combustible substances.



SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

HAZARDOUS AND/OR OTHER RELEVANT COMPONENTS	CAS No.	OEL (mg/m3)	OEL (ppm)	STOEL (mg/m3)	STOEL (PPM)	OEL Type
2-BUTOXYETHANOL	111-76-2	120	25			CL S
XYLENE	1330-20-7	435	100	650.	150.	RL+ S

(CL/RL = Controlled/Recommended level 'S' = Skin annotation)

SAPMA Rating 3-H-E PPE : Respirator and Eye protection
Inhalation In case of insufficient ventilation, use suitable respiratory protection.
Skin Use barrier cream and impervious gloves.
Eyes Use face shield & goggles or full face respirator/hood. Avoid direct contact.
Ingestion Observe the rules for hygiene. Wash before eating, drinking or smoking.
 OEL Type : Mixture - See tables in Sections 2 and 8



SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	Water based dispersion	Odour	Typical
Boiling Point	>100°C	Flash Point	n/a °C (derived)
Water solubility	miscible	Fat Solubility	Oil : miscible

SECTION 10. STABILITY AND REACTIVITY

Stable under normal conditions
 No reaction with fire-fighting water

SECTION 11. TOXICOLOGICAL INFORMATION

No carcinogenic, mutagenic or genetic effects established
 LD50 Oral: >500 mg (derived)

SECTION 12. ECOLOGICAL INFORMATION

May have short term environmental effects. Contain, monitor & remove

SECTION 13. DISPOSAL INFORMATION

Use reputable waste disposal contractors. Exercise caution in disposal of used containers.


SECTION 14. TRANSPORT INFORMATION

UN Number Not applicable. Not classified as dangerous for transport



SECTION 15. REGULATORY INFORMATION

EC no. : n/a
 EC Classification : Not classified as hazardous
 S2 - Keep out of reach of children. (Retail sales items)



SECTION 16. OTHER INFORMATION

IN CASE OF ANY DISCOMFORT ALWAYS SEEK MEDICAL ADVICE.

This MSDS conforms with General Administrative Regulations of 6 Sept.1996 (ISO-11014/ANSIZ400.1.1996)
OELs derived from OHS Act Regulations for Dangerous Chemical Substances of 25 Aug.1995 (EH-42)
SAPMA Rating - South African Paint Manufacturers Association Guide to Health Hazards (SABS ARP 006:1991)
All information is given in good faith but without guarantee in respect of accuracy.
No responsibility is accepted for errors or omissions or the consequences thereof.