



INTERNATIONAL SYSTEMS **TDS – North America**

METALUX 2™ Anti Static Degreaser

Technical Support (800) 328-4892
Website: www.chemspecpaint.com

9287 Smucker Road. Orrville, Ohio 44667

TD Sheet CS152 rev. 8/13/07

- Description:** Specifically formulated solvent blend designed to prevent the build up of static. Recommended for use on substrates prone to static build up such as plastic bumper covers. (Polypropylene)
- Product and Additives:** METALUX 2™ Silicone Remover 9020
METALUX 2™ Anti Static Degreaser 9145
- Application Process:** Clean thoroughly at least 3 to 4 times, each time using fresh Silicone Remover 9020 to ensure that the surface is clean and free of contamination Use a clean silicone free rag to apply. Do not place rag on opening of container as contamination could occur. Pour silicone remover onto rag or into a separate container and use from this container and then discard. Wipe in one direction followed up with a separate clean rag in the same direction. Clean article in sections.
Allow to evaporate and dry thoroughly.
Now wipe in one direction with Anti Static Degreaser 9145 with a clean cloth making sure to dry thoroughly.
- Health & Safety:** Flammable. No smoking. Contains VOC's therefore avoid breathing in vapours. Avoid contact with skin, wear gloves. Is a skin and eye irritation. Keep away from children.