



PROFESSIONAL QUALITY

Automotive Basecoat



Date issued 15/03/2007

9204 : WHITE



Flammable



Harmful



SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product Code: 9204	Product Name: METALUX 2 WHITE	UN No.: 1263
CAS No.: Not applicable	EC No.: Not applicable	
Company Name: <u>SOUTHAFRICA</u> Chemical Specialities (Pty) Ltd 320 South Coast Road Rossburgh Durban 4094	Company Name: <u>AUSTRALIA</u> ChemSpec Coatings (Pty) Ltd 52-54 Chard Road Brookvale, NSW	Company Name: <u>UNITED STATES OF AMERICA</u> ChemSpec USA, Inc. 9287 Smucker Road Orrville, Ohio 44667
Telephone: +27 31 450 8800	+61 02 9907 1425	+1 330 669 8512
Facsimile: +27 31 450 8930	+61 02 9907 1465	+1 330 669 3965
Contact: Group Technical Manager techservice@chemspecpaint.com www.chemspecpaint.com	techservice@chemspecpaint.com	+1 800 328 4892 (Toll Free) techservice@chemspecpaint.com

SECTION 2. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Class: PAINT or PAINT RELATED
Classification: F Xn R Phrases R11,20,36,66,67 S Phrases S02,13,16,26,43A,46,51
Comment: OEL Type: Mixture - See tables in Sections 2 and 8

	<u>% m/m</u>	<u>EC Labels</u>	<u>CAS No.</u>	<u>EC No.</u>
HAZARDOUS AND/OR OTHER RELEVANT COMPONENTS				
N-BUTANOL	<5 %	Xn	71-36-3	603-004-00-6
XYLENE	<12.5 %	Xn	1330-20-7	601-022-00-9
TOLUENE	<12.5 %	F Xn	108-88-3	601-021-00-3
ISOBUTYL ALCOHOL	<5 %	Xi	78-83-1	603-108-00-1

SECTION 3. HAZARDS IDENTIFICATION

SAPMA Health Rating: 2-MODERATE - Temporary or minor injury possible even if treatment given
Inhalation: Irritating, narcotic. Formaldehyde may be released during curing.
Skin: HARMFUL BY CONTACT.
Eyes: Irritating - may cause damage if not give prompt attention.
Ingestion: Harmful if swallowed. Can affect CNS. Systemic poison.

No carcinogenic, mutagenic or genetic effects established
May have short term environmental effects. Contain, monitor & remove

SECTION 4. FIRST AID MEASURES

Inhalation: Move to fresh air. In severe cases seek medical attention.
Skin: Use hand cleaner/soap & water. Remove contaminated clothing. If any discomfort get medical attention
Eyes: Rinse well with water. Seek medical advice if discomfort persists.
Ingestion: Wash mouth with plenty of water. Do NOT induce vomiting. Seek medical advice.

SECTION 5. FIRE FIGHTING MEASURES

Highly flammable with toxic fumes.
Containers can burst in a fire. Can form explosive vapour/air mixture. Static discharge hazard!
Foam. Dry powder. Fog to cool and control. Do NOT use water jets.
Cool containers in case of fire.

SECTION 6. ACCIDENTAL RELEASE MEASURES - SEE ALSO SECTIONS 5, 8, 13

Contain & collect. Use an inert - NOT Sawdust. Keep out of drains and sewers.



PROFESSIONAL QUALITY

Automotive Basecoat



SECTION 7. HANDLING AND STORAGE

Store only in designated places.
No open flames. No smoking. No sparks.
Keep containers cool. Avoid free fall of liquid - use earthing.
Subject to local bylaws.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

HAZARDOUS AND/OR OTHER RELEVANT COMPONENTS:

	<u>CAS No.</u>	<u>OEL</u> (mg/m ³)	<u>OEL</u> (ppm)	<u>STOEL</u> (mg/m ³)	<u>STOEL</u> (PPM)	<u>OEL</u> Type
N-BUTANOL	71-36-3	150	50	150	50	RL S
XYLENE	1330-20-7	435	100	650.	150.	RL +S
TOLUENE	108-88-3	188	50	560	150	RL +S
ISOBUTYL ALCOHOL	78-83-1	150	50	225	75	RL

(CL/RL = Controlled/Recommended level 'S' = Skin annotation)

SAPMA Rating:

Inhalation:

2-H-E PPE : Respirator and Eye protection.

Skin:

Ensure adequate ventilation or use respiratory protection. Ventilate curing areas/ovens properly.

Eyes:

Avoid direct contact. Use barrier cream and impervious gloves.

Ingestion:

Avoid any form of direct contact. Do not touch eyes with dirty hands or gloves.

Observe the rules of hygiene. Wash before eating, drinking or smoking.

OEL Type : Mixture - See tables in Sections 2 and 8



SAPMA - E

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	Viscous liquid	Odour:	Pungent
Boiling Point:	>35°C	Flash Point:	<23°C (derived)
Water solubility:	--	Fat Solubility:	--

SECTION 10. STABILITY AND REACTIVITY

Stable under normal conditions
Could generate static - USE EARTHING

Inert - no reaction with fire-fighting water.

SECTION 11. TOXICOLOGICAL INFORMATION

No carcinogenic, mutagenic or genetic effects established
LD50 Oral: t.b.e. (Derived)

SECTION 12. ECOLOGICAL INFORMATION

May have short term environmental effects. Contain, monitor & remove

SECTION 13. DISPOSAL INFORMATION

Use reputable waste disposal contractors. Exercise caution in disposal of used containers.

SECTION 14. TRANSPORT INFORMATION

UN Number	1263		
Shipping Name	PAINT or PAINT RELATED MATERIAL		
IMO Class	3.2	Packing Group	II
Action Code	127		
HazChem	3[Y]E		
Kemler Code	30		





PROFESSIONAL QUALITY

Automotive Basecoat



SECTION 15. REGULATORY INFORMATION

EC No.:	-	n/a	
F Xn	-	R Phrases R11,20,36,66,67	S Phrases S02,13,16,26,43A,46,51
R11	-	Highly flammable	
R20	-	Harmful by inhalation.	
R36	-	Irritating to the eyes	
R66	-	Repeated exposure may cause skin drying or cracking	
R67	-	Vapours may cause drowsiness and dizziness.	
S2	-	Keep out of reach of children. (Retail sales items)	
S13	-	Keep away from food, drink and animal feeding stuffs	
S16	-	Keep away from sources of ignition - No smoking	
S26	-	In case of contact with eyes, rinse immediately with plenty of water and seek medical advice	
S43A	-	In case of fire, use water fog, foam or powder - Do not use water jets!	
S46	-	If swallowed seek medical advice immediately and show this container or label.	
S51	-	Use only in well ventilated areas	



Flammable



Harmful

SECTION 16. OTHER INFORMATION

TAKE PRECAUTIONARY MEASURES AGAINST STATIC DISCHARGES.
IN CASE OF ANY DISCOMFORT ALWAYS SEEK MEDICAL ADVICE.

This MSDS conforms with General Administrative Regulations of 6 Sept.1996 (ISO-11014/ANSIZ400.1.1996)
OELs derived from OHS Act Regulations for Dangerous Chemical Substances of 25 Aug.1995 (EH-42)
SAPMA Rating - South African Paint Manufacturers Association Guide to Health Hazards (SABS ARP 006:1991)
All information is given in good faith but without guarantee in respect of accuracy.
No responsibility is accepted for errors or omissions or the consequences thereof.

(Date of issue : 15/03/2007

Date of analysis : 15/03/2007)