



INTERNATIONAL SYSTEMS **TDS – North America**

METALUX 2™ 2K Thinners

Technical Support (800) 328-4892
Website: www.chemspecpaint.com

9287 Smucker Road. Orrville, Ohio 44667

TD Sheet CS121 rev. 8/13/07

- Description:** METALUX 2™ 2K Thinners are designed exclusively to be used in the METALUX 2™ range of 2K Primers, Clears and 2K Color systems.
- Product and Additives:**
- 2K Thinner Fast 1177: For spot and panel repairs or cooler temperature. >20°C / 68°F.
- 2K Thinners Normal 1159: For treatment of large vehicles within the temperature of 20°C - 25°C / 68° F – 77°F.
- 2K Thinner Slow 1171: For treatment of large vehicles within the temperature range of 25°C - 40°C / 77° F – 105°F.
- 2K Low VOC Thinner 9710: Special medium drying solvent used to maintain correct VOC limits in METALUX 2™ 2K product group. Also used in Low VOC regulated areas.
- Basic Raw Materials:** Various solvents.
- Mixing Ratio:** Adhere to the mixing ratios specified in the technical data sheets of the above products.
Note: Keep 2K Thinners sealed when not in use.
- Health & Safety:** Reference text on label. Flammable – keep away from sources of ignition. No smoking. Do not breathe in spray. In case of insufficient ventilation, wear suitable respiratory equipment.